

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory-Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)
CONSERV SG80 FABRIC SOFTENER

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

NA = Not Applicable NIA = No Information Available

Manufacturer's Name Sunburst Chemicals, Inc.	Emergency Telephone Number 1-866-303-6943 (7 days/24 hours)
Address (Number, Street, City, State, and ZIP Code) 220 W. 86th St. Bloomington, MN 55420	Telephone Number For Information (952)884-3144
	Date Prepared 05-26-11
	Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Di (hydrogenated tallow) dimethyl ammonium chloride			LC50 >5000 mg/kg	
Coco di (hydroxyethyl) methyl ethoxylated ammonium chloride			LD50 >2000 mg/kg	

Section III - Physical/Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O=1)	
Vapor Pressure (mm Hg.)	NA	Melting Point	120° F.
Vapor Density (AIR=1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility In Water Dispersible.			
Appearance and Odor Light blue solid, slight odor.			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) None	Flammable Limits	LEL NA	UEL NA
Extinguishing Media Water CO2, Dry chemical.			
Special Fire Fighting Procedures Spray containers to keep cool.			
Unusual Fire and Explosion Hazards Containers exposed to extreme heat may rupture and spill.			

HMIS		NFPA		
1 HEALTH	HEALTH HAZARD	FIRE HAZARD	SPECIFIC HAZARD	REACTIVITY
0 FLAMMABILITY	4 Deadly	Flash Points	Oxidizer OX	4 May detonate
0 REACTIVITY	3 Extreme danger	4 Below 73°F (Boiling pt. below 100°F)	Acid ACID	3 Shock and heat may detonate
A PERSONAL PROTECTION	2 Hazardous	3 Below 73°F (Boiling pt. at/above 100°F) and/or at/above 73°F - not exceeding 100°F	Alkali ALK	2 Violent chemical change
	X 1 Slightly hazardous	2 Above 100°F, Not Exceeding 200°F	Corrosive COR	1 Unstable if heated
	0 Normal material	1 Above 200°F	Use NO WATER	X 0 Stable
		X 0 Will not burn	Radioactive	

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	
Incompatibility (Materials to Avoid) None.			
Hazardous Decomposition or Byproducts None.			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Routes(s) of Entry:	Inhalation?	Skin?	Ingestion?
	NO	NO	NO
Health Hazards (<i>Acute and Chronic</i>) ACUTE - skin and eye irritation. <u>INGESTION</u> - nausea, stomach pain, diarrhea. CHRONIC - NIA.			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NIA	NIA	NIA
Signs and Symptoms of Exposure <u>EXTERNAL</u> - redness and irritation. <u>INTERNAL</u> - foul taste, burning mouth and throat, stomach pain.			
Medical Conditions Generally Aggravated by Exposure Open sores or wounds.			
Emergency and First Aid Procedures <u>EXTERNAL</u> - thoroughly rinse with water for at least 15 minutes. Get medical attention irritation persists. <u>INTERNAL</u> - drink a large quantity of milk or water. Get immediate medical attention.			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Absorb spilled material with an absorbent material such as clay, sawdust, or sand. Sweep up as much of this as possible and place in a sealed, labeled container or in a proper landfill. Thoroughly rinse the affected area with water.	
Waste Disposal Method Spilled material should be collected as above for disposal in a landfill according to Federal, State, and Local regulations. Any rinsing of the affected area should also be in accordance with Federal, State and Local regulations.	
Precautions to Be Taking in Handling and Storing Keep tightly closed when not in use. Store in a cool place.	
Other Precautions Wipe up spills to prevent slippery floors. Keep away from children.	

Section VIII - Control Measures

Respiratory Protection (<i>Specify Type</i>) Not generally required.		
Ventilation	Local Exhaust NA	Special NIA
	Mechanical (<i>General</i>) NIA	Other NIA
Protective Gloves Rubber or vinyl recommended.	Eye Protection Safety glasses, goggles recommended.	
Other Protective Clothing or Equipment Rubber or vinyl apron recommended.		
Work/Hygienic Practices Always wash hands after using.		